



## J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

<b>TERMINAL PART NUMBER</b>	SPS-82T-187
<b>STRIP LENGTH (MM)</b>	5.2

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
0.75 mm <sup>2</sup> + 0.75 mm <sup>2</sup>	1.60	3.00	*	5.90	82N
0.75 mm <sup>2</sup> + 1.25 mm <sup>2</sup>	1.70	3.00	*	5.90	82N
					133N
1.25 mm <sup>2</sup> + 1.25 mm <sup>2</sup>	1.85	3.00	*	5.90	133N

### COMMENTS:

\* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

### GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05  
CONDUCTOR WIDTH - +/- 0.05  
INSULATION HEIGHT - N/A  
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
MS	PDS
19-03-07	19-03-07