



J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

| | |
|-----------------------------|------------|
| TERMINAL PART NUMBER | SXF-41-0.7 |
| STRIP LENGTH (MM) | 3.5 |

| APPLICABLE WIRE SIZE | CONDUCTOR BARREL | | INSULATION BARREL | | TENSILE (NEWTONS) |
|----------------------|------------------|-------|-------------------|-------|-------------------|
| | HEIGHT | WIDTH | HEIGHT | WIDTH | |
| 20 AWG | 1.10 | 2.00 | * | 3.40 | 65N |
| 18 AWG | 1.15 | 2.00 | * | 3.40 | 80N |
| 16 AWG | 1.25 | 2.00 | * | 3.40 | 100N |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

COMMENTS:

* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05
CONDUCTOR WIDTH - +/- 0.05
INSULATION HEIGHT - N/A
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

| | |
|--------------|--------------|
| Prepared by: | Approved by: |
| AJS | MS |
| 29-01-01 | 29-01-01 |