



## J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

<b>TERMINAL PART NUMBER</b>	SYF-001-0.6
<b>STRIP LENGTH (MM)</b>	2.6

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
28 AWG	0.60	1.50	*	1.80	9.8N
26 AWG	0.65	1.50	*	1.80	14.7N
24 AWG	0.70	1.50	*	1.80	19.6N
22 AWG	0.75	1.50	*	1.80	34.3N

### COMMENTS:

\* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

### GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05  
CONDUCTOR WIDTH - +/- 0.05  
INSULATION HEIGHT - N/A  
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
AJS	MS
29-01-01	29-01-01