



## J.S.T. (U.K.) LTD. CRIMP SPECIFICATIONS

<b>TERMINAL PART NUMBER</b>	SZF/M-01-0.7
<b>STRIP LENGTH (MM)</b>	5.0

APPLICABLE WIRE SIZE	CONDUCTOR BARREL		INSULATION BARREL		TENSILE (NEWTONS)
	HEIGHT	WIDTH	HEIGHT	WIDTH	
26 AWG	0.80	1.60	*	2.60	19.6N
24 AWG	0.85	1.60	*	2.60	29.4N
22 AWG	0.85	1.60	*	2.60	44.1N
20 AWG	0.95	1.60	*	2.60	63.7N

### COMMENTS:

\* INSULATION CRIMP HEIGHT IS DEPENDANT ON THE SPECIFICATION OF THE WIRE USED.

CRIMP HEIGHTS SPECIFIED ARE FOR GUIDANCE ONLY AND MAY VARY DEPENDING ON THE WIRE CONSTRUCTION AND TOLERANCE.

### GENERAL TOLERANCE:

CONDUCTOR HEIGHT - +/- 0.05  
CONDUCTOR WIDTH - +/- 0.05  
INSULATION HEIGHT - N/A  
INSULATION WIDTH - +/- 0.10

FOR SPECIFIC WIRES PLEASE CONTACT J.S.T. (U.K.) LTD.

Prepared by:	Approved by:
AJS	MS
29-01-01	29-01-01